

## SETUP SHEET (SIGHT)



12 12 16 5 11 11 16 5 7				•		
Name:		Date:		E	Event:	
City:	State:	Track:				
Track ☐ Indoor ☐ Tight ☐ Smooth Conditions ☐ Outdoor ☐ Open ☐ Rough	☐ Hard Packed ☐ Blue Groove ☐ Loose/Loamy ☐ Dry	⊎ Wet	☐ Low Bite☐ Med Bite	☐ High Bite☐ Other		
Front Suspension	Differentials		Acker	man	Bump Steer	
Toe:	_ Front: □ Standard □ Smart		Lon	g	Q 5 Up Down	
Ride Height:	_   Spring Wire Dia:		Sho	urt O	ор Down	_
Camber:	_ Qty of Springs:			Ā		
Caster:	_ Ramp Plate:					3
Sway Bar:	_ Grease:					1
Piston/Oil:	_ Diff Fluid:			ВА	Out	side
Spring:	_					side 3
Limiter/Droop:	_ Center: ☐ Standard ☐ Sma	rt				
Overall Shock Length:	– Spring Wire Dia: ——		//////////////////////////////////////			
Steering Ackerman:	' "					
Bump Steer:	, , ,					
Camber Link:						
Shock Location:			Notes:			
Receiver Battery Type:	_					
, , , , , , , , , , , , , , , , , , , ,						
Rear Suspension						
Toe:						
Anti-Squat:						7  -
Ride Height:		_				
Camber:					3—	
Rear Hub Spacing:		_		DСВА	1—	
Sway Bar:						
Piston/Oil:			H			
Limiter/Droop:					Outside Inside	3
Overall Shock Length:						0
Camber Link:		_				
Shock Location:		_				
Rear Diff Fluid:						
Engine			Notes:			
Engine:						
Glow Plug:						
Pipe/Header:						la a sut
Clutch Shoes ar	nd Springs Info	Tires	Type		Compound	Insert
		Front:				
		Rear:				
		Notes: .				