

## 1. General Description

This Document contains the log data of a read out logfile. It shows what happened with the specified vbar unit during the latest time

Version of PC Software	<b>5.3.1 22.05.2012</b>
Date	<b>Thu Oct 04 23:57:06 CEST 2012</b>
Serial	<b>1410034282</b>
Prod Date	<b>13.8.2012 7:40</b>
Firmware	<b>5.3</b>
Patchlevel	<b>1</b>

## 2. Chronological List of Events

▶	0:16	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.



✓	9:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	9:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	9:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	9:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	9:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	9:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	10:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	10:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	10:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	10:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	10:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	10:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	11:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	11:12	Raised Vibration Level 2	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	11:22	High Vibration Level 2	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✗	11:32	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	11:42	Raised Vibration Level 1	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	11:50	Antenna Switched 0	The Signal from one of the satellites was missing. The Main receiver is switched over to the other connector. In Case of a single receiver connected, one frame was lost.
⚠	11:52	High Vibration Level 1	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
⚠	12:02	High Vibration Level 1	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✗	12:10	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	12:22	Raised Vibration Level 0	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	12:22	Raised Vibration Level 9	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	12:32	High Vibration Level 9	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✓	12:42	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	12:52	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✓	13:09	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✓	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:01	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:08	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✓	0:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	1:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	1:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	1:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:36	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
✓	1:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:55	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	2:05	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	2:14	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
✗	2:24	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
⚠	2:33	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
✓	2:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	2:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	3:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	3:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	3:21	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
⚠	3:31	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.

✓	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✓	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:01	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:08	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✓	0:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:48	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
⚠	0:57	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
⚠	1:07	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
✗	1:16	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	1:26	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
✓	1:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	1:45	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
✓	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✓	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:07	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✓	0:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:37	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	0:47	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:57	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
✓	1:07	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	1:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

▶	1:26	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	1:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	1:45	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Safe flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	1:55	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:05	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:09	Bank 2 Loaded	Bank 2 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	2:17	Bank 1 Loaded	Bank 1 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
✔	2:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:37	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:47	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:57	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	3:02	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	3:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:02	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:08	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:42	Bank 2 Loaded	Bank 2 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:52	Bank 1 Loaded	Bank 1 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
✔	1:02	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:22	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:27	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	1:37	Bank 2 Loaded	Bank 2 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	1:44	Bank 1 Loaded	Bank 1 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.





✔	6:34	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:44	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:54	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:04	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:14	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:24	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:34	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:44	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Bank 1 Loaded	Bank 1 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:07	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:37	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:47	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:57	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:07	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:37	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	1:45	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
▶	1:55	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	2:05	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	2:09	Bank 2 Loaded	Bank 2 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	2:14	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.

⚠	2:24	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	2:30	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
⚠	2:33	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	2:43	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	2:45	Bank 2 Loaded	Bank 2 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	2:53	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
⚠	3:02	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✖	3:12	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
⚠	3:21	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
⚠	3:31	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	3:41	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
✖	3:50	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
⚠	4:00	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✖	4:10	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	4:19	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
✔	4:29	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:39	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:49	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	4:58	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
⚠	5:07	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	5:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:03	Bank 2 Loaded	Bank 2 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:08	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory

✔	0:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:16	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	1:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:36	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	1:45	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	1:55	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:05	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:14	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	2:24	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
⚠	2:33	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered by manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:02	Bank 2 Loaded	Bank 2 was loaded from the non volatile memory. This can be triggered by manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:08	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✔	1:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	3:21	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	3:31	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	3:31	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
⚠	3:41	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	3:50	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	4:00	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	4:09	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
▶	4:10	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	4:19	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
⚠	4:29	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	4:39	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:49	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:59	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	5:04	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
✔	5:14	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

▶	5:22	Antenna Switched	The Signal from one of the satellites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
✔	5:32	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:42	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:52	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	5:55	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
✔	6:05	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:02	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:08	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:24	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
▶	2:33	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.

▶	2:43	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✘	2:53	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	2:58	Antenna Switched	The Signal from one of the satellites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
✘	3:02	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
✘	3:12	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	3:21	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	3:31	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	3:41	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	3:50	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	4:00	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	4:10	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	4:19	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	4:29	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	4:35	Antenna Switched	The Signal from one of the satellites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
✘	4:38	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	4:41	Antenna Switched	The Signal from one of the satellites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
⚠	4:48	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	4:58	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	5:07	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	5:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	5:36	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	5:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✔	6:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Bank 3 Loaded	Bank 3 was loaded from the non volatile memory. This can be triggered my manual bankswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel.
▶	0:07	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:37	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:47	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:57	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:07	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:37	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:47	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:57	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:07	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	2:33	The Cyclic Ring is active	If the agility of a Heli is set to the possibilities of the mechanic and aerodynamic limits, this did not happen. However in 3D Flying the agility cannot set high enough to fulfill the pilots needs. So this limiter is in action dependant on the flown actions. If it is active very often, there is a potential problem with the mechanics. Using lighter blades will help increasing the natural agility preventing hitting the cyclic ring all the time.
▶	2:33	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
✘	2:34	Aileron Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handleled on ground, or on very hard landings or very extreme Vibrations.
⚠	2:34	Tail Sensor shows no actual Signal	This is an plausibility check. If the Heli starts to vibrate, this shall at least have effect to all sensors. If one of the Sensors do not show the Signal, it may point to a specific problem, not necessary with this sensor, but a general problem.
✘	2:36	Aileron Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handleled on ground, or on very hard landings or very extreme Vibrations.
✘	2:36	Elevator Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handleled on ground, or on very hard landings or very extreme Vibrations.
✘	2:43	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations

⚠	2:53	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	3:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	3:21	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	3:31	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
⚠	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered by manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
⚠	0:04	Init Failed, retrying...	The Init process of the sensors is very sensitive to movements of the heli or from other external disturbances, i.e. Voltage jumps and glitches. This can lead to a failed initialization. In this Case it is repeated. If this repeats itself all the time, this can point to a defective sensors.
⚠	0:07	Init Failed, retrying...	The Init process of the sensors is very sensitive to movements of the heli or from other external disturbances, i.e. Voltage jumps and glitches. This can lead to a failed initialization. In this Case it is repeated. If this repeats itself all the time, this can point to a defective sensors.
⚠	0:09	Init Failed, retrying...	The Init process of the sensors is very sensitive to movements of the heli or from other external disturbances, i.e. Voltage jumps and glitches. This can lead to a failed initialization. In this Case it is repeated. If this repeats itself all the time, this can point to a defective sensors.
⚠	0:09	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
⚠	0:10	Init Failed, retrying...	The Init process of the sensors is very sensitive to movements of the heli or from other external disturbances, i.e. Voltage jumps and glitches. This can lead to a failed initialization. In this Case it is repeated. If this repeats itself all the time, this can point to a defective sensors.
⚠	0:12	Init Failed, retrying...	The Init process of the sensors is very sensitive to movements of the heli or from other external disturbances, i.e. Voltage jumps and glitches. This can lead to a failed initialization. In this Case it is repeated. If this repeats itself all the time, this can point to a defective sensors.
⚠	0:13	Init Failed, retrying...	The Init process of the sensors is very sensitive to movements of the heli or from other external disturbances, i.e. Voltage jumps and glitches. This can lead to a failed initialization. In this Case it is repeated. If this repeats itself all the time, this can point to a defective sensors.
⚠	0:19	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	0:29	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:39	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:49	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:59	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:09	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:19	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:29	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:39	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:49	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:59	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:09	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.









✔ 16:1 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 16:2 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 16:3 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 16:4 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 16:5 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 17:0 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 17:1 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 17:2 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 17:3 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 17:4 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 17:5 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 18:0 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 18:1 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 18:2 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔ 18:3 9	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.